## Additional Terms & Conditions (ATC)

- I. The subject item is **proprietary** in nature and hence, only OEM <u>M/S RK CONTROL</u> and it's <u>authorized seller/distributor/dealer/channel partner</u> is eligible to participate in this bid.
- II. <u>Authorized seller/distributor/dealer/channel partner</u> shall have to submit valid authorization letter from OEM on OEM's letterhead failing which offer is liable to be rejected.
- III. Guarantee/Warrantee: The offered material shall be guaranteed against any manufacturing defect and poor workmanship for a period of 18 months from the date of supply or 12 months from the date of commissioning, whichever is earlier. In case the material fails during guarantee period due to defective material or bad workmanship, you will have to replace/rectify the same free of cost. The guarantee certificate should indicate our order number and your invoice number. <u>Guarantee/Warrantee Certificate</u> shall be submitted along with dispatch documents at no extra cost to NFL.

SI. No.	Item Code	Item Detail	UoM	Qty
1	IA2141081	Spare Body Completely Assembled and tested with all internals(Seat,Plug with Stem,Cage,Seal Rings,Gland Packings and all Gaskets)ready to be fitted with existing Actuator Model No:A3-150H for Control Valve 15-FV-01. Valve Model No:10- 835I.Size:4" X 3".Rating:1500 RTJ. All necessary specifications is in <b>Annexure 2</b> attached below.	ST	1
2	IA5141031	Spare Body Completely Assembled and Tested with all internals(Seat,Plug with Stem,Cage,Seal Rings,Gland Packings and all gaskets)ready to be fitted with existing actuator model:A4-075H for control valve 15-HV-03. Valve Model No:10- 835I.Size:2" X 1.5".Rating:1500 RTJ. All necessary specifications is in <b>Annexure 1</b> attached below.	ST	1

# Item Specification & Quantity

### Annexure

### Specifications for Spare Body completely assembled and tested with all Internals for 15-HV-03.

	1)	Item	:	Spare Body Completely asssembled & tested with all internals (Seat, Plug with Stem and Pin,Cage,Seal Rings,Gland Packings & all gaskets) ready to be fitted
	2)	Item Code	:	with Existing RK Control actuator Model:A4 -075H. IA5141031
		Previous PO Ref.of Original valve procurement	:	PC1754BIA081858E Dtd:01/04/2010
	4)	Original valve-SI.No	:	10110966
	5)	Valve Model	:	10-8351
	6)	Actuator Model	:	A4-075H
	7)	Valve Size / Trim Size	:	2"(50 NB ) / 1.5"
	8)	Body form	:	Globe
	9)	End connection Style	:	RTJ Groove
1	10)	Rating	:	ANSI 1500
1	1)	Body Material	:	Carbon Steel A216 Gr WCB
1	12)	Bonnet type	:	Normalising (Finned)
1	13)	Service	• :	Boiler Feed Water
1	14)	IBR Certification	:	Yes.required
. 1	15)	End to end dimension of valve Body	:	428 mm

#### Note:

1) Spare Valve body shall be Completely assembled and tested with all internals.

2) Party shall submitt Material test certificate for Body and Trim indicating chemical composition and physical properties,

3) Manufacturer's Pressure test certificate(for leakage and body, bonnet and gland) along-with despatch documents.

4) Party shall provide Interchangeability Certificate for proper fitting of Supplied Spare body with Existing Actuator .

5) Party shall provide IBR Certificate .

## Annexure 2

Specifications for Spare Body completely assembled and tested with all Internals for 15-FV-01.

1) Item	:	Spare Body Completely asssembled & tested with all internals (Seat, Plug with		
i) item		Stem and Pin,Cage,Seal Rings,Gland Packings & all gaskets) ready to be fitted		
		with existing RK Control actuator Model : A3 -150H.		
2) Item Code	:	IA2141081		
<ol> <li>Previous PO Ref.of Original valve procurement</li> </ol>	:	PC1754BIA081858E Dtd:01/04/2010		
4) Original valve SI.No.	:	10110965		
5) Valve Model	:	10-8351		
6) Actuator Model	:	A3-150H		
7) Valve Size / Trim Size	:	4"(100 NB ) / 3"		
8) Body form	:	Globe		
9) End connection Style	:	RTJ Groove		
10) Rating	:	ANSI 1500		
11) Body Material	:	Carbon Steel A216 Gr WCB		
12) Bonnet type	:	Normalising (Finned)		
13) Service	:	Boiler Feed Water		
14) IBR Certification	:	Yes.required		
15) End to end dimension of valve Body	:	549 mm		

#### Note:

1) Spare Valve body shall be Completely assembled and tested with all internals.

2) Party shall submitt Material test certificate for Body and Trim indicating chemical composition and physical properties.

3) Party shall submitt manufacturer's Pressure test certificate (for leakage and body, bonnet and gland) and along-with despatch documents.

4) Party shall provide Interchangeability Certificate for proper fitting of Supplied Spare body with Existing Actuator .

5) Party shall provide IBR Certificate .