ATC: BIA221198

Scope of Supply

SI. No.	Item Code	Item Description	UoM	Quantity
1	JA6140955	Actuator Repair Kit for Control Valve Tag No 346PIC-300	ST	1
2	JA6140956	Packing Set for Control Valve Tag No 346PIC-300	ST	2
3	JA6140957	Gasket Set for Control Valve Tag No 346PIC-300	ST	2
4	JA6140958	Trim Set for Control Valve Tag No 346PIC-300	ST	1
5	JA6140959	New Complete Control Valve, Tag No: 346-PIC-300 for HRU Natural Gas pressure control. Detail specification is attached at Annexure-I.	NO	1

Additional Terms & Conditions (ATC)

- I. Party should submit detailed technical catalogue for quoted items with decoding statement along with the offer.
- II. Guarantee/Warrantee: The offered material shall be guaranteed against any manufacturing defect and poor workmanship for a period of 18 months from the date of supply or 12 months from the date of commissioning, whichever is earlier. In case the material fails during guarantee period due to defective material or bad workmanship, you will have to replace/rectify the same free of cost. The guarantee certificate should indicate our order number and your invoice number. Guarantee/Warrantee Certificate shall be submitted along with dispatch documents.

ANNEXURE 1

1. MAIN NG CONTROL VALVE SPECIFICATIONS (346-PIC-300)

	TITLE	NFL'S SPECIFICATIONS	VENDCIR CONFIRMATION
SL NO			/REMARK
1	TAG NO.	MAIN NG VALVE	
2	QUANTITY	1 COMPLETE VALVE	
3	SERVICE	NG PRESSURE CONTROL	
4	FLUID STATE	GAS	
5	SPECIFIC GRAVITY: NOR/MAX	0.55 / 0.75	
6	MOLECULAR WEIGHT: MIN/MAX	16 / 21.65	
7	FLOW RATE: Nm3/Hr MIN/NOR/MAX	800/4000/7500	
8	INLET PRESSURE KG/CM2 MIN/NOR/MAX	10/15/20	
9	OUTLET PRESSURE KG/CM2 MIN/NOR/MAX	0.50/1.5/3.00	
10	INLET TEMPRATURE DEG C MIN/NOR/MAX	15/50/70	
11	DP ACTUATOR SIZING Kg/cm2 NOR/MAX	13.5/20	
12	MAX SHUT OFF DP Kg/cm2	20	
13	LINE SIZE : IN/OUT	4" / 8"	
14	CV REQUIRED/CALCULATED	VENDOR TO SPECIFY	
15	CV SELECTED	VENDOR TO SPECIFY	
16	NOISE LEVEL	< 90 DB	
VALVE			
17	VALVE SIZE/ RATING	2" / #300	
18	VALVE TYPE	GLOBE	
19	END CONNECTION / RATING	RF FLANGE / CLASS #300	
20	FLANGE FACE TO FACE DISTANCE	EXISTING = 130MM, VENDOR TO SPECIFY	
21	BODY MATERIAL/RATING	A216 WCB / #300	
TRIM			
22	PLUG TYPE MATERIAL	SS316 HARD FACE	
23	CHARECTERISTICS	LINEAR	
24	CAGE MATERIAL	SS316, PARTY TO SPECIFY	
25	SEAT MATERIAL	SS316 HARD FACE STELLITE	
26	TYPE OF BONNET	PLAIN	
27	LEAKAGE CLASS	CLASS IV OR BETTER	
28	PACKING	VENDOR TO SPECIFY SUITABLE FOR ABOVE SERVICE CONDITIONS	
ACTUA	TCOR		
29	ACTUATOR TYPE	DIAPGRAGM SPRING RETURN	
30	FAIL SAFE ACTION	VALE CLOSES	
31	INST TUBING/CONNECTION	12 MM/NPT	
32	HAND JACK	REQUIRED, PARTY TO SPECIFY	
33	AVALIABLE PNEUMATIC SUPPLY	MAX 6 KG/CM2 AVAILABLE	
34	POSITIONER TYPE / MAKE	SMART POSITIONER WITH DIGITAL DISPLAY, POSITIONER FEEDBACK & CONFIGURABLE FROM HART COMM. AND KEY PAD/ BUTTONS ON FRONT, VENDOR TO SPECIFY	
35	INPUT SIGNAL/ACTION	4 TO 20 mA/DIRECT	
36	AIR FILTER REGULATOR	REQUIRD, PLAKA, SMC, NORGEN MAKE	
37	GAUGES	REQUIRED	
SPARE	18		

100 CG-2

38	DIAPHRAGM		1NO.	
39	ACTUATOR REPAIR KIT		1SET	
40	40 TRIM(PLUG+STEM+CAGE+SEAT)		1SET	
41	41 TRIM SEAL RING		2NOS.	
42	TRIM/BONNET GASKET		2 sets	
43	GLAND PACKING		2 Sets	
44	POSITIONER		1 NO.	
COMPA	NION FLANGES			
45	COMPANION FLANGES FOR S	UPPLIED	2 NOS. 2", MATERIAL CS (A-	
45	CONTROL VALVE		105), DIAMENSION AS PER ANSI B16.5	
NOTE:				
THE OFFER SHALL BE COMPLETE WITH RELATED PRODUCT CATALOGUE, DIMENSIONAL		TED PRODUCT CATALOGUE, DIMENSIONAL		
46	DRAWINGS ETC.			
47	ALL THE CALCULATION AND I	DATA SHEET FO	OR CONTROL VALVE CV TO BE SUBMITTED.	
48	ALL THE DEVIATIONS ARE TO BE CLEARLY INDICATED.			
Following documents/certificates are required along with the material				
49	9 SEAT LEAKAGE TEST REPORT.			
50	BODY PRESSURE TEST REPORT.			
51	GUARANTEE/WARRANTY CERTIFICATE.			

	2. MAIN NG CONTRO	OL VALVE BYPASS VALVE SPECIFICATIONS (346-PI	C-30 ∮)
SERVI	CE CONDITIONS :		
SL NO.	TITLE	NFL'S SPECIFICATIONS	VENDOR'S CONFIRMATION/REMARK
1	TAG NO.	MAIN NG VALVE BYPASS VALVE	
2	QUANTITY	1	
3	SERVICE	NG PRESSURE CONTROL	
4	FLUID STATE	GAS	
5	SPECIFIC GRAVITY: NOR/MAX	0.55 / 0.75	
6	MOLECULAR WEIGHT: MIN/MAX	16 / 21.65	
7	FLOW RATE: Nm3/hR MIN/NOR/MAX	00/800/800	
8	PRESSURE KG/CM2 INLET/OUTLET	10/15/20	
9	OUTLET PRESSURE KG/CM2 MIN/NOR/MAX	0.50/1.0/1.0	
10	INLET TEMPRATURE DEG C MIN/NOR/MAX	15/50/70	
11	DP ACTUATOR SIZING NOR/MAX	14.0/20.0	
12	LINE SIZE: IN/OUT	1" / 1"	
13	CV REQUIRED/CALCULATED	VENDOR TO SPECIFY	
14	CV SELECTED	VENDOR TO SPECIFY	
15	NOISE LEVEL	< 90 DB	
VALVI	BODY		
16	VALVE SIZE/ RATING	2" / #300	
17	ТҮРЕ	PRESSURE REGULATING VALVE (MANUAL VALVE), PRESSURE ADJUSTABLE FROM 0.6 KG/CM2 to 1.5 KG/CM2, SET PRESSURE = 0.8 KG/CM2	
18	ENDCONNECTION /RATING	VENDORTOSPECIFY	
19	FLANGE FACETO FACE DISTANCE	EXISTING = 130MM, VENDOR TO SPECIFY	
20	BODY MATERIAL/RATING	A216 WCB CLASS / #300	
21	SEAT TYPE/ MATERIAL	PARTY TO SPECIFY	
ACTU.			
22	ACTUATOR TYPE	DIAPGRAGM	
SPAR	ES		
23	DIAPHRAGM	1NO.	· ·
24	ACTUATOR REPAIR KIT	1SET	
25	INTERNAL PARTS	1SET	
COMP	PANION FLANGES		

Minto

21.06.23

COMPANION FLANGES FOR	2 NOS. 2", MATERIAL CS (A-		
SUPPLIED CONTROL VALVES	105), DIAMENSION AS PER ANSI B16.5		
THE OFFER SHALL BE COMPLETE WITH RELATED PRODUCT CATALOGUE, DIMENSIONAL			
DRAWINGS ETC.			
ALL THE CALCULATION AND DATA SHEET FOR CONTROL VALVE TO BE SUBMITTED.			
ALL THE DEVIATIONS ARE TO BE CLEARLY INDICATED.			
Following documents/certificates are required along with the material			
SEAT LEAKAGE TEST REPORT.			
BODY PRESSURE TEST REPORT.			
GUARANTEE/WARRANTY CERTIFICATE.			
	THE OFFER SHALL BE COMPLETE WITH RELIDRAWINGS ETC. ALL THE CALCULATION AND DATA SHEET FOR ALL THE DEVIATIONS ARE TO BE CLEARLY IN ING documents/certificates are required alough the search of the se	THE OFFER SHALL BE COMPLETE WITH RELATED PRODUCT CATALOGUE, DIMENSIONAL DRAWINGS ETC. ALL THE CALCULATION AND DATA SHEET FOR CONTROL VALVE TO BE SUBMITTED. ALL THE DEVIATIONS ARE TO BE CLEARLY INDICATED. Ing documents/certificates are required along with the material SEAT LEAKAGE TEST REPORT. BODY PRESSURE TEST REPORT.	

201.01.23

Self-Certification Form: Make In India (Local Content)

(On Party/Company's Letter Head)

Tender Ref. No.:
To M/s National Fertilizers Limited, Vijaipur-Guna (M.P)-473111
Sub: Self Certification as per clause 9(a) of Revised Public Procurement (Preference to Make in India Order, 2017 of DPIIT dated 16.09.2020
Sir,
This is to certify that M/s
I also certify that the bidder M/s has not been debarred by any procuring entity from violation of this order.
The address is as below, where the local content/value addition is made: [Factory Address]
For M/s
Authorized Signatory
(with company seal & Name)

Model Clause Certificate: Public Procurement

Certificate regarding Procurement from a Bidder of a country which shares a land border with India

(On Company's Letter Head)